



FEATURES

- CO₂, humidity and temperature measurement
- Dual wavelength NDIR CO₂ sensor (Non-Dispersive Infrared) for superior stability.
- User operated CO₂ calibration
- Data Hold & Max/Min/STEL/TWA function
- Adjustable auto power off timer
- Internal CO₂ alarm buzzer
- Backlight display function
- Datalogging up to 32,000 sets
- USB interface ,PC software included

SPECIFICATIONS

Measurement Range:

CO₂: 0 ~ 30000 ppm

Temperature: 0 to 50°C (32 to 122°F)

Humidity: 0 ~ 100%RH

Accuracy:

CO₂: ± (75 ppm + 3% of reading)

(0 ~ 5000 ppm)

Temperature: ± 1.0°C

Humidity: ± 4.5%RH

Resolution: 1 ppm, 0.1°C/0.1°F, 0.1%RH

Response Time: 20 seconds

Battery Type: 9V alkaline battery

Battery life:

Approximately 10 hours normal use
(alkaline battery)

Operating Condition: 0°C to 50°C(< 90%RH)

Storage Condition: -20°C to 60°C(< 75%RH)

Dimensions: 226.5 x 65 x 38.5 mm

Weight: 273 g

Accessories:

9V Battery 、 Instruction Manual 、
micro USB cable 、 Windows software 、
Carrying case.

★**NEW!**



CENTER[®]
CENTER TECHNOLOGY CORP.

4F, No.415, Jung-Jeng Road, Shu-Lin Dist.,
New Taipei City 238, Taiwan
TEL: 886-2-26763926 E-Mail : center@centertek.com
FAX: 886-2-26763925 http : //www.centertek.com

* The specifications and other information in this catalogue are subject to change without prior notice.

Distributed by: